## COREtec Plus XL

## US Patent # 9,156,233 Technical Specifications

**Description:** Patented Premium Engineered COREtec Plus® XL Luxury Vinyl Long Plank Floating Floor with

Attached Cork Underlayment

Warranty: Lifetime Limited Residential Wear Warranty

Lifetime Limited Structural Warranty
Lifetime Limited Waterproof Warranty
10 Year Limited Commercial Wear Warranty

**Installation:** Float, Glue Down

Size/Packaging: 228mm x 1828mm x 8.3 mm (± 0.2 mm) Planks

2.5m<sup>2</sup>/carton, 6 planks per carton, 21kgs each carton, 36 ctns per pallet

Pattern Repeat: 4 planks

Construction: 1.8 mm virgin PVC (0.5 mm/20 mil wear surface)

5.0 mm (± 0.2 mm) core (Limestone, virgin PVC, wood and bamboo dust).

1.5 mm cork underlayment

Edges/Ends: Micro-bevel

Wear Finish: 2 coats UV-cured acrylic

**Gloss Level**: 8% - 10%

TEST DATA

ASTM-E648 Critical Radiant Flux: Meets or exceeds, Class 1

ASTM E492-09 Impact Sound Conduction: IIC 62 db
ASTM E90-09 Airborne Sound Conduction: STC 62 db
ASTM C518 Thermal Resistance: R Value - 0.57

NALFA 3.2 Thickness Swell:

NALFA 3.3 Xenon Light Resistance:

Class 4, Heavy Commercial

NALFA 3.9 Caster Chair: Class 3, Commercial

NALFA 3.10 Surface Bonding: 1.31 N/mm - Exceeds Class 3 Commercial

Requirement

ASTM C 1028-96 Static Coefficient of Friction: 0.68 (slip resistance) Passes ADA/OSHA standard

**ASTM F-970-07 Static Load Limit:** 0.005 inch – Passes at 500 psi

ASTM-F2753 Rolling Load Over Resilient FC: 0.024 inch

ASTM F 1514 Color Resistance to Heat: Meets <8.0 Delta E Requirement
ASTM F 1515 Color Resistance to Light: Meets <8.0 Delta E Requirement

Certifications: CARB Compliant

GREENGUARD GOLD Certified